

## Xo700 SB

Product Reference	Xo700
ENISO 20345:2011	SB SRC
Sizes	36-47
Weight (s. 41)	480 gr.

**Model description:** Leather shoe, water repellent, white, cambrella lining, antistatic, shock proof, antislip, steel toe, SB, PU/PU sole.

**Application areas:** Catering, medical personnel.

**Precaution and maintenance of the shoe:** To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.



		Description	Measure Unit	Result	EN345 required
Complete shoe	Protection of toes: composite tip resistant to: A shock of 200 J Pressure of 1500 kg	Impact resistance (Clearance after shock)	Mm	15	>14
		Compressive strength (after clearance compression)	Mm	17	14
	Anti-shock system: Low-Density polyurethane and profile of the heel	Shock absorption in heel	J	>30	>20
Upper	leather, water repellent, white	Permeability to water vapor	Mg/m <sup>2</sup> hour		>0,8
	Thickness 1,6mm	Permeability coefficient	Mg/cm <sup>2</sup>		>20
		Water repellent	Minute		<60
Front	Thickness 1,2mm	Permeability coefficient	Mg/cm <sup>2</sup>		>30
Lining	Cambrella, grey	Permeability to water vapor	Mg/cm <sup>2</sup> hour		>2
Back	Thickness 1,0mm	Permeability coefficient	Mg/cm <sup>2</sup>		>30
Insole	Antistatic, absorbent, resistant to abrasion and to exfoliation	Abrasion resistance	Cycles	>400	>400
Outsole	Antistatic double density polyurethane injected directly onto the upper	Abrasion resistance (volume loss)	Mm <sup>3</sup>	110	<150
	Shock Absorption, anti-slip, abrasion resistant, mineral oils and weak acids	Oil resistance (volume variation AV)	%	+1,0	<+12
		Coefficient of adhesion of the outsole	-	0,19	>0,15

*Our shoes are constantly evolving, the technical data above may change.*

*All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.*